

SAFETY DATA SHEET

Version #: 01 Issue date: 21-March-2023 Revision date: -Supersedes date: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name or designation of the mixture	JURID Brake Fluid
Registration number	-
Synonyms	DOT 3 – All grades, DOT 4 - grades with Wet Boiling Points < 165 °C.
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Identified uses	Hydraulic fluid in automotive brake/clutch system.
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Manufacturer/Supplier	
Company name	Federal-Mogul Global Aftermarket EMEA bv
Address:	Prins Boudewijnlaan 5
	B-2550 Kontich
	Belgium
Contact person:	Mario Garelli – Product Manager Braking Products EMEA
	E-mail: mario.garelli@driv.com
Telephone:	+39 045 8281 354
1.4. Emergency Telephone:	INFOTRAC: 001-352-323-3500
	Belgium Poison Center (Centre Antipoison): +32 070 245 245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Reproductive toxicity	Category 2	H361d - Suspected of damaging the unborn child.

2.2. Label elements

Contains:

Label according to Regulation (EC) No. 1272/2008 as amended

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate

Hazard pictograms



Signal word

Warning

Hazard statements H319

H361d

Causes serious eye irritation. Suspected of damaging the unborn child.

Precautionary statements

Prevention P102

P264

Keep out of reach of children. Wash thoroughly after handling.

Response

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P305 + P351 + P338	IF IN EYES: Rins and easy to do. C		ter for several minutes. Remo	ove contact lenses	s, if present
P337 + P313		rsists: Get medical a	advice/attention.		
Storage	None.				
Disposal					
P501	Dispose of conter	nts/container in acco	ordance with local/regional/na	tional/internationa	l regulations.
Supplemental information on the label	None.				
2.3. Other hazards	(EC) No 1907/200 The mixture does REACH Article 59 greater than 0.1% The mixture does accordance with t	06, Annex XIII. not contain any sub 0(1) for having endoo 0 by weight. not contain any sub he criteria set out in	nces assessed to be vPvB / P ostances included in the list es crine disrupting properties at a ostances having endocrine dis Commission Delegated Reg 05 at a concentration equal to	stablished in account a concentration ec srupting properties ulation (EU) 2017/	rdance with qual to or in 2100 or
SECTION 3: Composition/	information on	ingredients			
3.2. Mixtures					
General information					
Chemical name	%	CAS-No. / EC No	. REACH Registration No.	Index No.	Notes
Triethylene glycol monobutyl	ether 20 - 29,9	143-22-6	01-2119475107-38-XXXX	602 102 00 0	
		205-592-6	01-2113-73107-30-77777	003-183-00-0	
	ication: Eye Dam.	1;H318			
	•	1;H318	, Eye Irrit. 2;H319: 20 % <= C		
	•	1;H318		< 30 %	
Specific Concentration	Limits: Eye Dam. 15 - 24	1;H318 1;H318: C >= 30 %, 111-46-6	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX	< 30 %	
Specific Concentration	Limits: Eye Dam. 15 - 24	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX	< 30 %	
Specific Concentration Diethylene glycol Classif Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate	Limits: Eye Dam. 15 - 24 Fication: Acute Tox	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2 .4;H302;(ATE: 500 30989-05-0 250-418-4	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX mg/kg bw)	< 30 % 603-140-00-6	
Specific Concentration Diethylene glycol Classif Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate	Limits: Eye Dam. 15 - 24 fication: Acute Tox 5 - 20	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2 .4;H302;(ATE: 500 30989-05-0 250-418-4	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX mg/kg bw)	< 30 % 603-140-00-6	
Specific Concentration Diethylene glycol Classif Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate Classif Butyl Polyglycol Classif	Limits: Eye Dam. 15 - 24 ication: Acute Tox 5 - 20 ication: Repr. 2;H3 5 - 10 ication: Eye Dam.	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2 .4;H302;(ATE: 500 30989-05-0 250-418-4 361d 9004-77-7 500-012-0 1;H318	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX mg/kg bw) 01-2119462824-33-XXXX 01-2119475115-41-XXXX	< 30 % 603-140-00-6 - -	
Specific Concentration Diethylene glycol Classif Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate Classif Butyl Polyglycol Classif	Limits: Eye Dam. 15 - 24 ication: Acute Tox 5 - 20 ication: Repr. 2;H3 5 - 10 ication: Eye Dam.	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2 .4;H302;(ATE: 500 30989-05-0 250-418-4 361d 9004-77-7 500-012-0 1;H318	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX mg/kg bw) 01-2119462824-33-XXXX	< 30 % 603-140-00-6 - -	
Specific Concentration Diethylene glycol Classif Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate Classif Butyl Polyglycol Classif	Limits: Eye Dam. 15 - 24 ication: Acute Tox 5 - 20 ication: Repr. 2;H3 5 - 10 ication: Eye Dam.	1;H318 1;H318: C >= 30 %, 111-46-6 203-872-2 .4;H302;(ATE: 500 30989-05-0 250-418-4 361d 9004-77-7 500-012-0 1;H318	, Eye Irrit. 2;H319: 20 % <= C 01-2119457857-21-XXXX mg/kg bw) 01-2119462824-33-XXXX 01-2119475115-41-XXXX	< 30 % 603-140-00-6 - - < 30 %	#

Specific Concentration Limit	its: Repr. 1B;H3	60D: C >= 3 %	
2 (2 Dutors with over) other al	0.0	440.04 5	04 0440475404 44 V

2-(2-Butoxyethoxy)ethanol	0 - < 3	112-34-5 203-961-6	01-2119475104-44-XXXX 603-096-00-	8 #
Classificatio	n: Eye Irrit. 2;H			

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

#: This substance has been assigned Community workplace exposure limit(s).

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in
percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.
4.1. Description of first aid meas	ures
Inhalation	Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Get medical attention if any discomfort continues.

JURID Brake Fluid

4.2. Most important symptoms	Severe eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort.
and effects, both acute and	Defats the skin. Central nervous system. May cause abdominal discomfort if swallowed.
delayed	Headaches, dizziness and nausea.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Will burn if involved in a fire.
5.1. Extinguishing media	
Suitable extinguishing media	Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Water mist.
Unsuitable extinguishing media	Water jet.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	Use standard firefighting procedures and consider the hazards of other involved materials. Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Follow standard emergency procedure. Do not breathe mist/vapours. Wear appropriate personal For non-emergency protective equipment (See Section 8). personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid For emergency responders contact with skin and eyes. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS. Avoid discharge into drains, water courses or onto the ground. 6.2. Environmental precautions Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is 6.3. Methods and material for possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product containment and cleaning up recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. 6.4. Reference to other For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS. sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Avoid contact with skin and eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Provide adequate ventilation. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep container in a well-ventilated place. Store between 15°C - 30°C (60°F - 86°F). Store away from incompatible materials (see section 10 of the SDS).
incompationities	Storage class (TRGS 510): 6.1C (Combustible substances of acute toxicity, category 3/hazardous substances that are toxic or produce chronic effects)
7.3. Specific end use(s)	Hydraulic fluid in automotive brake/clutch system.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Germany. DFG MAK List (adviso in the Work Area (DFG)	ory OELs). Commission for the	Investigation of Health Hazards	of Chemical Compounds	
Components	Туре	Value	Form	

components	туре	value	1 onn	
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)	TWA	67 mg/m3	Vapour and aerosol.	
		10 ppm	Vapour and aerosol.	

Туре	Value	Form
TWA	44 mg/m3	Vapour and aerosol.
	10 ppm	Vapour and aerosol.
the Ambient Air at the Workpla Type	ace Value	Form
AGW	67 mg/m3	Vapour and aerosol.
	10 ppm	Vapour and aerosol.
AGW	50 mg/m3	Vapour and aerosol.
	10 ppm	Vapour and aerosol.
AGW	44 mg/m3	Vapour and aerosol.
	10 ppm	Vapour and aerosol.
in Directives 91/322/EEC, 2000 Type	0/39/EC, 2006/15/EC, 200 Value	9/161/EU, 2017/164/EU
STEL	101,2 mg/m3	
	15 ppm	
TWA	67,5 mg/m3	
	10 ppm	
TWA	50,1 mg/m3	
	10 ppm	
Value	Assessment factor	Notes
50 mg/kg bw/day	40	Repeated dose toxicity respiratory tract irritation
5 mg/kg bw/day	40	Repeated dose toxicity
		respiratory tract irritation
1,33 mg/kg bw/day	30	
30.1 ma/m3		Repeated dose toxicity
30,1 mg/m3 7,5 mg/kg bw/day	120	Repeated dose toxicity Repeated dose toxicity
7,5 mg/kg bw/day	120	Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg	120 40	Repeated dose toxicity Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3	120 40 10	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg	120 40	Repeated dose toxicity Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3	120 40 10	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day	120 40 10 40	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation Repeated dose toxicity
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day 12 mg/m3	120 40 10 40 10	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day 12 mg/m3 5 143-22-6)	120 40 10 40 10 210	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation Repeated dose toxicity respiratory tract irritation
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day 12 mg/m3 5 143-22-6) 125 mg/kg/day	120 40 10 40 10	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation Repeated dose toxicity respiratory tract irritation
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day 12 mg/m3 5 143-22-6)	120 40 10 40 10 210 40	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation Repeated dose toxicity respiratory tract irritation
7,5 mg/kg bw/day 125 mg/kg 117 mg/m3 12,5 mg/kg 12 mg/m3 21 mg/kg bw/day 12 mg/m3 5 143-22-6) 125 mg/kg/day 117 mg/m3	120 40 10 40 10 210 40 10 40	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation Repeated dose toxicity respiratory tract irritation Repeated dose toxicity Repeated dose toxicity
	Type AGW AGW AGW AGW in Directives 91/322/EEC, 2000 Type STEL TWA TWA TWA gical exposure limits noted for the tandard monitoring procedures. Value I-5) 50 mg/kg bw/day 40,5 mg/m3 5 mg/kg bw/day 60,7 mg/m3 77-3)	10 ppm the Ambient Air at the Workplace Type Value AGW 67 mg/m3 AGW 50 mg/m3 AGW 50 mg/m3 AGW 10 ppm STEL 101,2 mg/m3 TWA 67,5 mg/m3 10 ppm 10 ppm TWA 50,1 mg/m3 10 ppm 10 ppm Standard monitoring procedures. 10 ppm tandard monitoring procedures. 10 ppm t-5) 50 mg/kg bw/day 40 40,5 mg/m3 50 mg/kg bw/day 40 60,7 mg/m3 40 60,7 mg/m3

Components	Value	Assessment factor	Notes
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Short-term, Local, Inhalation	83 mg/kg bw/day 67,5 mg/m3 101,2 mg/m3	24	Repeated dose toxicity respiratory tract irritation respiratory tract irritation
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	2,22 mg/kg bw/day 50,1 mg/m3	18	Repeated dose toxicity
Butyl Polyglycol (CAS 9004-77-7)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	208 mg/kg 195 mg/m3	24 6	Repeated dose toxicity Repeated dose toxicity
Diethylene glycol (CAS 111-46-6)			
Long-term, Local, Inhalation Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	60 mg/m3 43 mg/kg bw/day 44 mg/m3	2 105	respiratory tract irritation Repeated dose toxicity
Triethylene glycol monobutyl ether (CAS 143-2	2-6)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	208 mg/kg/day 195 mg/m3	24 6	Repeated dose toxicity Repeated dose toxicity
Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] ortho	borate (CAS 30989-05-0)		
Long-term, Systemic, Dermal	16,7 mg/kg	60	Repeated dose toxicity
licted no effect concentrations (PNECs)			
Components	Value	Assessment factor	Notes
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)			
Freshwater	1,1 mg/l	1000	
Marine water	0,11 mg/l	10000	
Secondary poisoning	56 mg/kg	90	Oral
Sediment (freshwater)	4,4 mg/kg		
Sediment (marine water) Soil	0,44 mg/kg 0,32 mg/kg		
STP	200 mg/l	10	
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)	200 mg/		
Freshwater	12 mg/l	100	
Intermittent releases	12 mg/l		
Marine water	1,2 mg/l	1000	
Secondary poisoning	0,09 g/kg	200	Oral
Sediment (freshwater)	44,4 mg/kg		
Sediment (marine water)	0,44 mg/kg		
Soil	2,1 mg/kg		
STP	10000 mg/l	1	
Butyl Polyglycol (CAS 9004-77-7)			
Freshwater	4,5 mg/l	100	
Marine water	0,31 mg/l	1000	Oral
Secondary poisoning Sediment (freshwater)	111 mg/kg 6,6 mg/kg	90 1000	Oral
Sediment (marine water)	0,66 mg/kg	10000	
Soil	1,32 mg/kg	10000	
STP	500 mg/l	10	
Diethylene glycol (CAS 111-46-6)			
Freshwater	10 mg/l	10	
Intermittent releases	10 mg/l		
Marine water	1 mg/l	100	
Sediment (freshwater)	20,9 mg/kg		
Sediment (marine water)	2,09 mg/kg		
Soil STP	1,53 mg/kg 199,5 mg/l	10	
Triethylene glycol monobutyl ether (CAS 143-2	-		
Freshwater	2 mg/l	50	
Intermittent releases	8,4 mg/l	50	
Marine water	0,2 mg/l	500	
		90	Oral
Secondary poisoning	111 mg/kg	90	Ulai
	111 mg/kg 7,7 mg/kg	90	Orai

JURID Brake Fluid

STP	200 mg/l	10		
Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)				
Freshwater	0,211 mg/l	1000		
Intermittent releases	2,112 mg/l			
Marine water	0,021 mg/l	10000		
Sediment (freshwater)	0,76 mg/kg			
Sediment (marine water)	0,076 mg/kg			
Soil STP	0,028 mg/kg 100 mg/l	10		
Exposure guidelines	100 mg/r			
Germany TRGS 900 Limit V	alues: Skin designation			
2-(2-Methoxyethoxy)etha	-	Can be absorbed through the skin.		
8.2. Exposure controls				
Appropriate engineering controls	applicable, use process enclosur maintain airborne levels below re	be used. Ventilation rates should be matched to conditions. If res, local exhaust ventilation, or other engineering controls to ecommended exposure limits. If exposure limits have not been vels to an acceptable level. Provide easy access to water supply		
Individual protection measures,				
General information		hould be chosen according to the CEN standards and in e personal protective equipment.		
Eye/face protection	Wear safety glasses with side sh	ields (or goggles). Use eye protection conforming to EN 166.		
Skin protection				
- Hand protection	with breakthrough time of >480 r gloves with breakthrough time of chemical-resistant protective glo industrial hygiene practices and the working conditions and alway type of glove for each task and the specifications. The use of type-B minimum protection against inter suitable option for the product in for applications involving mechan	tant gloves. Full contact: Glove material: Butyl rubber. Use gloves ninutes minutes. Minimum glove thickness 0.3 mm. Nitrile. Use > 480 minutes. Minimum glove thickness 0.2 mm. Always wear ves that comply with EN 374 to handle this product. Observe good wash gloves with soap and water before removing them. Assess ys consult your glove supplier for information on the most suitable he required material, thickness, and breakthrough time gloves in accordance with EN 374 is recommended as a mittent or splash contact. Consult your supplier to find the most question. The requirements of EN 388 must be taken into account hical hazards with the risk of abrasion or incision. The must be taken into consideration for tasks involving thermal		
- Other	Wear appropriate clothing to pre-	vent repeated or prolonged skin contact.		
Respiratory protection		or when the product is heated, use suitable respiratory equipment ory protection should meet standard EN 14387.		
Thermal hazards	When material is heated, wear g	loves to protect against thermal burns.		
Hygiene measures	and before eating, drinking, and/ equipment to remove contamina	ygiene measures, such as washing after handling the material or smoking. Routinely wash work clothing and protective nts. Observe any medical surveillance requirements.		
Environmental exposure controls	process equipment should be ch environmental protection legislat	informed of all major releases. Emissions from ventilation or work ecked to ensure they comply with the requirements of ion. Fume scrubbers, filters or engineering modifications to the ssary to reduce emissions to acceptable levels.		
SECTION 9: Physical and	chemical properties			

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Colourless to amber.
Odour	Mild.
Melting point/freezing point	< -50 °C (< -58 °F)
Boiling point or initial boiling point and boiling range	> 205 °C (> 401 °F)
Flammability	Will burn if involved in a fire.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Property has not been measured.
Explosive limit – upper (%)	Property has not been measured.
Flash point	> 100 °C (> 212 °F)
JURID Brake Fluid	

Auto-ignition temperature	> 280 °C (> 536 °F)
Decomposition temperature	300 °C (572 °F)
рН	> 7 - < 10,5
Kinematic viscosity	> 5 - < 10 cSt Approximate (20 °C (68 °F))
Solubility	
Solubility (water)	Soluble in water. Miscible with: Ethanol.
Partition coefficient (n-octanol/water) (log value)	<2
Vapour pressure	1 mbar
Density and/or relative density	
Relative density	> 1,01 - < 1,06
Vapour density	Property has not been measured.
Particle characteristics	Not applicable, material is a liquid.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
9.2.2. Other safety characteristic	cs
Evaporation rate	0,01 (Butyl acetate = 100)
SECTION 10: Stability and	I reactivity
10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable under normal temperature conditions. Glycol Ethers can form peroxides on storage – do not distil to dryness.
10.3. Possibility of hazardous reactions	Will not occur.
10.4. Conditions to avoid	Avoid exposure to high temperatures or direct sunlight. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
10.6. Hazardous	Fire or high temperatures create: Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

decomposition products

Inhalation	Glycol does not easily form a vapour at normal temperatures. Therefore, it must be heated or misted before inhalation exposure can occur.
Skin contact	Prolonged or repeated contact may dry skin and cause dermatitis.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms	Severe eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort. Defats the skin. Central nervous system. May cause abdominal discomfort if swallowed. Headaches, dizziness and nausea.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product	Species	Test Results	
JURID Brake Fluid (CAS	Mixture)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 3000 mg/kg	
Oral			
LD50	Rat	> 5000 mg/kg	
Components	Species	Test Results	
2-(2-Butoxyethoxy)ethance	ol (CAS 112-34-5)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	2700 mg/kg	

Components	Species		Test Results
Oral	5.4		4500
LD50	Rat		4500 mg/kg
2-(2-Methoxyethoxy)ethanol (CAS	5 111-77-3)		
<u>Acute</u> Dermal			
LD50	Rabbit		8980 ml/kg
Oral	Rabbit		
LD50	Rat		6700 ml/kg
Diethylene glycol (CAS 111-46-6))		
Acute			
Oral			
LD50	Rat		16500 mg/kg
Triethylene glycol monobutyl ethe	er (CAS 143-2	2-6)	
Acute			
Dermal			
LD50	Rabbit		3540 mg/kg
Oral	_		
LD50	Rat		5300 mg/kg
Skin corrosion/irritation	Based on a	available data, the classification	criteria are not met.
Serious eye damage/eye irritation	Causes se	rious eye irritation.	
Respiratory sensitisation	Based on a	available data, the classification	criteria are not met.
Skin sensitisation	Based on a	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on a	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.		
Specific target organ toxicity - single exposure	Based on a	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Based on a	Based on available data, the classification criteria are not met.	
Aspiration hazard	Based on a	available data, the classification	criteria are not met.
Mixture versus substance information	No informa	No information available.	
11.2. Information on other haza	rds		
Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respe to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.		
Other information		Glycol ethers: Some glycol ethers cause adverse effects in animals that include the reproductive system, offspring, blood, kidney and liver.	
SECTION 12: Ecological i	nformation	1	
12.1. Toxicity	Based on a	Based on available data, the classification criteria are not met for hazardous to the aquatic environment.	
Components		Species	Test Results
Diethylene glycol (CAS 111-46-6))		
Aquatic			
Algae	EC50	Algae	> 6500 - < 13000 mg/l, 96 hours
	NOEC	Algae	100 mg/l, 72 hours
Acute			
Crustacea	EC50	Aquatic invertebrates	100000 mg/l, 24 hours
Fish	LC50	Fish	7520 mg/l, 96 hours
Chronic			
Crustana		A quatia invartabrataa	22011 mg/kg/D 21 days

Aquatic invertebrates

Aquatic invertebrates

JURID Brake Fluid

Crustacea

EC50

NOEC

33911 mg/kg/D, 21 days

> 8590 - < 24000 mg/l, 7 days

Components		Species	Test Results
			> 7500 - < 15000 mg/l, 21 days
Fish	NOEC	Fish	> 15380 - < 32000 mg/l, 7 days
Triethylene glycol monobutyl ethe	er (CAS 143-	22-6)	
Aquatic			
Acute			
Fish	LC50	Pimephales promelas	2400 mg/l, 96 hours
12.2. Persistence and degradability	Expected to be inherently biodegradable. Expected to be readily biodegradable. (OEC		bected to be readily biodegradable. (OECD 302B).
12.3. Bioaccumulative potentia	Potential	to bioaccumulate is low.	
Partition coefficient n-octanol/water (log Kow)			
JURID Brake Fluid		< 2	
2-(2-Butoxyethoxy)ethanol (C			
2-(2-Methoxyethoxy)ethanol Diethylene glycol (CAS 111-	•	7-3) -1,18 -1,47	
Triethylene glycol monobutyl			
Bioconcentration factor (BCF)	Not availa	able.	
12.4. Mobility in soil	This prod	uct is water soluble and may disper-	se in soil.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		sessed to be vPvB / PBT according to Regulation
12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with res to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater tha 0.1% by weight.		
12.7. Other adverse effects	None kno	wn.	
SECTION 13: Disposal co	nsiderati	ons	
13.1. Waste treatment methods			
Residual waste		ntainers or liners may retain some p ed of in a safe manner (see: Dispos	product residues. This material and its container mus sal instructions).
Contaminated packaging	Since em	ptied containers may retain product	residue, follow label warnings even after container i

Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	16 01 13* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

ADIX	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	Not assigned.
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
RID	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.

14.5. Environmental hazards 14.6. Special precautions for user ADN	No. Not assigned.
14.1. UN number 14.2. UN proper shipping name	Not regulated as dangerous goods. Not regulated as dangerous goods.
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
ΙΑΤΑ	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping name	Not regulated as dangerous goods.
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	-
14.6. Special precautions	Not assigned.
for user	-
IMDG	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	No.
EmS	Not assigned.
14.6. Special precautions for user	Not assigned.
14.7. Maritime transport in bulk	Not applicable.

14.7. Maritime transport in bulk Not a according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU or Not listed.	n major accident hazards involving dangerous substances, as amended
Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended. According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.
National regulations	
TA-LUFT	5.2.5 (Organic Substances)
Water hazard class	
AwSV	WGK1
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). CAS: Chemical Abstract Service.
	CEN: European Committee for Standardization.
	DNEL: Derived No-Effect Level.
	EC50: Effective Concentration, 50%.
	IATA: International Air Transport Association.
	IMDG: International Maritime Dangerous Goods.
	IMO: International Maritime Organization.
	LC50: Lethal Concentration, 50%.
	LD50: Lethal Dose, 50%.
	NOEC: No observed effect concentration.
	PBT: Persistent, bioaccumulative and toxic.
	PNEC: Predicted No-Effect Concentration.
	RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
	TWA: Time Weighted Average.
	vPvB: Very persistent and very bioaccumulative.
References	HSDB® - Hazardous Substances Data Bank
	ECHA: European Chemical Agency.
	Registry of Toxic Effects of Chemical Substances (RTECS)
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements,	
which are not written out in full	
under sections 2 to 15	H302 Harmful if swallowed.
	H318 Causes serious eye damage.
	H319 Causes serious eye irritation.
	H360D May damage the unborn child.
	H361d Suspected of damaging the unborn child.
This SDS contains revisions in the following section(s):	2, 3, 4, 6, 7, 8, 9, 11, 12, 15, 16.
Training information	Follow training instructions when handling this material.
Further information	UFI: C300-D0AQ-400U-2MRM, Grade: DOT 3
	UFI: PE00-E039-C00U-Q02V, Grade: DOT 4 – 230

The information provided on this data sheet was abstracted from supplier safety data sheets and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information is however, as of the date provided, true and accurate to the best of Federal-Mogul's knowledge, and should be used to make an independent determination of the methods to safeguard workers and the environment.